

3.5kW split system reverse cycle air conditioner featuring wireless connectivity, inverter compressor, DC fan motor with 12 fan speeds, concealed dimmable digital display, HEPA and ion filters, auto air swing (up, down), LCD remote, demand response capable. 3.5kW cooling/4.0kW heating capacity.

RRP AUS \$0.00



Product Details

FEATURES

Heating and cooling modes of operation
Provides year round comfort

Kelvinator Connect
Wireless connectivity.

LCD backlit wireless remote control
Easy access to all functionality combined with a large easy screen backlit to be clearly readable in all lighting conditions

5 year parts and labour warranty

Auto or Manual operation
Easy to set and forget or retain full user control

Follow Me command
Measures and controls the temperature where you are for personal comfort

24 hour timer
Program your air conditioner to turn on and off automatically

Inverter compressor technology
Electronic compressor control for maximum energy efficiency and minimum noise

Auto Air Swing
Air can be automatically directed up and down to distribute cooling or heating evenly

Sleep mode
Sleep mode automatically adjusts the temperature while you sleep for maximum comfort and minimum energy consumption

Auto restart
In the event of an interruption in power supply the unit will restart with the same settings that were selected prior to the power outage

BENEFITS

Comfort & convenience at the touch of your hands
Kelvinator Connect allows you to be smarter with your heating and cooling needs from any location with your smart device via the Kelvinator Home Comfort App. At your convenience, turn the unit on or off, change temperatures, control modes and adapt fan speeds to best meet your comfort needs.

Easy to use
One touch climate control is at your fingertips with a simple-to-use remote control

Superior comfort and control

With DC inverter technology you'll enjoy greater comfort, control and energy efficiency all year round

Easy to clean

The contemporary clean-face fascia not only looks good, it also minimises dust build-up on the front of the unit. Slim and compact, these air-conditioners are unobtrusive and will suit any interior style

Specifications

PRODUCT PROFILE

Domestic warranty details (yrs)	5
Type	reverse cycle

SPECIFICATIONS

Capacity cool watts	3500
Capacity Heat watts	4000
Current rating amps	10.5
Power Supply Connection Point	outdoor unit
Colour of fascia	White
Compressor type	rotary
Indoor sound pressure dBA high setting	47
Indoor sound pressure dBA low setting	22
Outdoor sound pressure dBA	54
Outdoor Sound Power dBA	64
Indoor air circulation max (ltr/s)	194
Ambient temperature range minimum	-15

SPECIFICATIONS

Ambient temperature range maximum	50
-----------------------------------	----

Moisture removal ltr/hour	1.3
---------------------------	-----

Energy star rating cooling	4.0
----------------------------	-----

Energy star rating heating	4.0
----------------------------	-----

Cooling EER	4.25
-------------	------

Heating COP	4.25
-------------	------

Refrigerant weight (g)	850
------------------------	-----

Refrigerant type	R32
------------------	-----

OUTDOOR UNIT DIMENSIONS

Width (mm)	765
------------	-----

Height (mm)	555
-------------	-----

Depth (mm)	303
------------	-----

INDOOR UNIT DIMENSIONS

Total width (mm)	802
------------------	-----

Total height (mm)	297
-------------------	-----

Total depth (mm)	189
------------------	-----

FEATURES

INSTALLATION REQUIREMENTS (PIPING AND WIRING)

Gas pipe size	12.7
---------------	------

FEATURES

Features - Air Conditioners	remote control,manual operation,air swing auto up/down,auto restart,fan mode,auto mode,air direction control,cooling mode,dry mode,self diagnosis,room temperature display,Heating Mode,low pressure detection,demand-response enabled,anti cold air function,Follow me,Silence,Sleep mode,Turbo,Wireless enabled
Filtration	dust,hepa,Ion Filter
Remote control type	LCD,back lit
Timer	24 hour
Anti corrosion treatment	gold shield
Fan speeds	low,medium,high,turbo,Auto,Silent
Display/ indicators	temperature,defrost

INDOOR UNIT PACKED DIMENSIONS

Shipping Volume (m3)	0.09
Shipping Weight (Kg)	11.3
Pack Dimensions Width (mm)	875

INSTALLATION REQUIREMENTS (PIPING AND WIRING)

Liquid pipe size	6.35
Maximum piping length vertical	10
Maximum piping length	25
Additional refrigerant required supplied charge length (g/m)	12
Maximum pipe length with supplied charge	5
Wires connecting indoor unit to outdoor unit	4

OUTDOOR UNIT PACKED DIMENSIONS

Shipping Volume (m3)	0.18
Shipping Weight (Kg)	30.7
Pack Dimensions Width (mm)	887

INDOOR UNIT PACKED DIMENSIONS

Pack Dimension Height (mm)	380
Pack Dimension Depth (mm)	285

OUTDOOR UNIT PACKED DIMENSIONS

Pack Dimension Height (mm)	610
Pack Dimension Depth (mm)	337

STUFFING QUANTITIES

20ft	76
40ft	160
40ft HC	192

Terms and Conditions

IMPORTANT

This is a guide of product dimensions only. For complete installation instructions, refer to the manual provided with product.

PRODUCT INFORMATION

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous product development, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes the products that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux Home Products Pty Ltd (Australia) and Electrolux (NZ) Ltd (New Zealand) will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Colours of products illustrated are as close as printing limitations allow. Electrolux will at all times comply with its obligations pursuant to law including Trade Practices (Australian Consumer Law) Act and Regulations.

WARRANTY

This warranty only applies to Appliances purchased and used in Australia or New Zealand and used in normal domestic applications and is in addition to (and does not exclude, restrict, or modify in any way) any non-excludable statutory warranties in Australia or New Zealand. All warranties are subject to the conditions set out in the warranty card accompanying the product when purchased.

ELECTROLUX HOME PRODUCTS AUSTRALIA

telephone: 1300 363 640

fax: 1800 350 067

email: customercare@electrolux.com.au

web: www.electrolux.com.au

ELECTROLUX HOME PRODUCTS NEW ZEALAND

telephone: 09 573 2230

fax: 09 573 2221

email: customercare@electrolux.co.nz

web: www.electrolux.co.nz