

*N 50, Wall-mounted canopy rangehood, 90 cm, Black
D94BHM1S5*



COOKING PASSION SINCE 1877



The coordinating and stylish Neff canopy rangehood is modern in design and keeps up with your cooking.

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ High Extraction Rate: ensures a clear view while cooking thanks to an efficient motor technology
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise – Our optimised motor guarantees a quiet cooking experience

Features

Technical Data

Typology : Wall-mounted
Length electrical supply cord : 130 cm
Height of the chimney : 583-912/583-1022 mm
Height of product, without chimney : 53 mm
Minimum distance above an electric cooktop : 600 mm
Minimum distance above a gas cooktop : 650 mm
Net weight : 13.4 kg
Type of control : Electronic
Number of power settings : 3-stages + intensive setting
Maximum output air extraction : 372 m³/h
Boost position output recirculating : 441 m³/h
Maximum output recirculating air : 337 m³/h
Boost position air extraction : 604 m³/h
Number of lights : 2
Noise level : 60 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242004268826
Connection Rating : 220 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Plug type : GARDY plug w/ earthing
Installation type : Wall-mounted



4 242004 268826

N 50, Wall-mounted canopy rangehood, 90 cm,
Black
D94BHM1S5



COOKING PASSION SINCE 1877

Features

- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 48.5 kWh/year
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: C

Design & Innovation

- 90 cm Chimney hood
- Appliance colour: black
- TouchControl for power and light

Safety and Quality

Power and Mode of Operation

- Extraction rate exhaust air according to EN 61591: max. normal use 372 m³/h, intensive 604 m³/h
- Noise min./max. Normal Level: 48/60 dB
- TouchControl (3 power levels plus intensive setting) with Electronic display
- Automatic intensive revert setting - 6 min
- With the Clean Air Plus recirculation kit (available as accessory) your appliances reaches:
Extraction rate in recirculation mode: Max. normal use: 337 m³/h
Intensive: 441 m³/h
Noise level in recirculation mode: Max. normal use: 70 dB(A) re 1 pW
Intensive: 74 dB(A) re 1 pW

Heating Functions

Cleaning

- Dishwasher safe metal grease filters

Convenience

- Suitable for ducted extraction and recirculation
- Accessories required for recirculated extraction: Recirculating kit

Dimensions (HxWxD)

- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
703 x 900 x 500 mm - mounting with outer chimney
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

Technical Information

- Power rating: 220 W
- Electrical cable length 1.3 m
- Wall Hood black
- Appliance width: 900 mm
- For wall mounted installation
- Electronic controls
- T34-NE3A
- Electronic controls with low-lift push buttons
- 3 power levels plus intensive setting via TouchControl
- Capacitor energy efficient
- 2 x 1.5W LED
- Extraction rate exhaust air according to EN 61591: max. 604 m³/h
- Maximum extraction 604 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)
- Max. extraction rate: 604 m³/h

* In accordance with the EU-Regulation No 65/2014

D94BHM1S5

[illegible]