



OR90SCG1X1

Freestanding Dual Fuel Cooker, 90cm

Classic

Feeding a crowd is a breeze with this stylish 90cm Fisher & Paykel Freestanding Cooker that lets you cook several dishes at once with its spacious gas cooktop and generous convection oven.

Brushed Stainless Steel with black glass



A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1300 650 590 W fisherpaykel.com

Dimensions

Depth	600mm
Height	898 - 946mm
Width	897mm

Features & Benefits

Quality and durability

Every detail has been carefully crafted, from the solid balanced door, durable cooktop trivets and large capacity oven.

Impressive capacity

With an extra large 140L capacity, this range has plenty of space for cooking multiple dishes at the same time.

Burner power & control

Instant and immediate control from the highest to the gentlest heat. The finely tuned cooktop controls let you sear and stir fry over powerful heat, or simmer a delicate sauce to perfection.

Even heat

Dishes on the top shelf turn out as perfectly as the ones on the bottom, due to our AeroTech™ convection system that circulates air evenly throughout the entire oven.

Easy to clean

Your cooktop simply needs a quick wipe to keep it looking good as new for years to come, as the gas cooktop is made from a single piece of stainless steel that contains spills. The oven door, its inner pane of glass and runners can also be removed for easy cleaning.

Safe and sound

The door and cavity cooling system keeps the heat on the inside, protecting your hands and surrounding cabinetry. The flame failure safety device automatically turns off the gas if the flame is accidentally extinguished.

Specifications

Accessories

Chromed shelf runners	1 set
Flat wire shelf	1
Full extension sliding shelves	Optional (part 578744)
Hob rear trim (optional)	60mm (part 81658)
Kick strip, stainless steel (optional)	Part 81661
Roasting Dish	•
Small pot support	1 (part 573752)
Square foot covers, stainless steel (optional)	1
Step down wire shelf	1
Wok stand	1 (part 534678 wire)

Cleaning

Acid resistant graphite enamel	•
Dishwasher safe trivets	•
Drop down grill element	•
Removable oven door/inner glass	•
Removable oven door/s	•
Removable shelf runners	•

Controls		Oven features		Safety	
Audio feedback	•	AeroTech™ technology	•	Advanced cooling system	•
Automatic cooking/minute timer	•	Full extension telescopic sliding shelves	Optional (part 578744)	Anti-tilt bracket	•
Celsius/Fahrenheit temperature	•	Internal light	2 x 25W halogen (side)	Balanced oven door	•
Electronic clock	•	Storage compartment	•	CoolTouch door	•
Interior light	•	True Convection	•	Flame failure system	•
Laser etched graphics	•	Twin cavity fans	•	Non-tip shelves	•
Turned stainless steel clock buttons	•			Spill containment	2.6L
Cooktop features		Oven functions		Style And Series	
Dishwasher safe trivets	•	Bake	•	Product Style	Classic
Gas Cooktop- Sealed range top	•	Defrost	•	Warranty	
LPG/Natural gas compatible	•	Fan Bake	•	Warranty	2 years
Cooktop performance		Fan forced	•	SKU	
Auxiliary burner (LPG)	1.1 - 3.9 MJ/h	Fan grill	•	SKU	81265
Auxiliary burner (natural gas)	1.1 - 3.9 MJ/h	Grill	•	The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © © Fisher & Paykel Appliances Ltd 2018	
Max burner power	16.2 MJ/h	Number of Functions	7		
Number of burners	5	Warm	•		
Rapid burner (LPG)	6.5 - 11.7 MJ/h	Oven performance		Other product downloads available at fisherpaykel.com	
Rapid burner (natural gas)	6.5 - 11.7 MJ/h	CoolTouch door	Double glazed	fisherpaykel.com	
Semi-rapid burner (LPG)	2.5 - 6.5 MJ/h	Grill	3000 W		
Semi-rapid burner (natural gas)	2.5 - 6.5 MJ/h	Shelf positions	6		
Total cooktop power	44.8 MJ/h	Total oven capacity	140 L		
Wok burner (LPG)	16.2 MJ/h	Usable capacity	121 L		
Wok burner (natural gas)	16.2 MJ/h	Power requirements			
Installation cutout dimensions		AMP draw	14 A		
Depth	600 mm	Supply frequency	50 Hz		
Width	900 mm	Supply voltage	220 - 240 V		