

*N 70, WALL-MOUNTED CANOPY RANGEHOOD, 90 CM, STAINLESS STEEL
D95BMP5N0*



The stylish Neff canopy rangehood is modern in design and keeps up with your cooking.

- ✓ Efficient Drive Motor – Quiet and energy-efficient motor for a calmer kitchen.
- ✓ Touch Control: An integrated flat surface control panel for smooth operation with a fingerswipe.
- ✓ Intensive Speed Setting: Increases the extraction rate when cooking steam is intense.
- ✓ Dimmer Function: Easily dim the light according to your mood with the touch of a finger.
- ✓ High Extraction Rate – ensures a clear view while cooking thanks to an efficient motor technology

Z50XXP0X0	Long Life odor filter (replacement)
Z51CBI2X4	Clean Air Standard recirculation kit
Z51CXC2N6	Clean Air Plus recirc. kit external
Z51CXI1X6	Clean Air Plus recirculation kit
Z51FXD2N1	Long Life recirculation kit external
Z51FXJ0X5	Long Life recirculation kit
Z53CBB2X4	Clean Air Standard odor filter (repl.)
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5861N0	Back panel stainless steel
Z5895N0	Stainless steel back panel 900 mm
Z5906N1	Chimney extension 1000 mm
Z5916N1	Chimney extension 1500 mm

Typology:	Wall-mounted
Length electrical supply cord:	130.0 cm
Height of the chimney:	582-908/568-1018 mm
Height of product, without chimney:	46 mm
Minimum distance above an electric cooktop:	600 mm
Minimum distance above a gas cooktop:	650 mm
Net weight:	17.9 kg
Type of control:	Electronic
Number of power settings:	3-stages + 2 intensive settings
Maximum output air extraction:	427 m³/h
Boost position output recirculating:	442 m³/h
Maximum output recirculating air:	343 m³/h
Boost position air extraction:	702 m³/h
Number of lights:	3
Noise level:	55 dB(A) re 1pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable stainless steel
EAN code:	4242004234906
Connection Rating:	145 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50; 60 Hz
Plug type:	Gardy plug w/ earthing
Installation typology:	Wall-mounted



*N 70, WALL-MOUNTED CANOPY RANGEHOOD, 90
CM, STAINLESS STEEL
D95BMP5N0*

- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 427 m³/h. Intensive 702 m³/h

Design & Innovation

- Wall Hood brushed steel
- Appliance colour: brushed steel
- TouchControl for power and light
- Softlight with Dimming function
- 3 x 1.5 Watt LED Lights

Power and Mode of Operation

- 3 power levels + 2 intensive levels via TouchControl
- Efficient BLDC-technology
- Extraction rate exhaust air according to EN 61591:
 - max. normal use 427 m³/h, intensive 702 m³/h
- With the Clean Air Plus recirculation kit (available as accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use: 343 m³/h
 - Intensive: 442 m³/h
 - Noise level in recirculation mode: Max. normal use: 66 dB(A) re 1 pW
 - Intensive: 70 dB(A) re 1 pW
 - Noise min./max. Normal Level: 45/55 dB

Cleaning

- Stainless steel filter covers, dishwasher safe

Convenience

- Automatic intensive revert setting - 6 min
- Automatic run on - 10 min
- Saturation display for filters

Dimensions (HxWxD)

- For wall mounted installation
- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm

Technical Information

- Suitable for ducted extraction and recirculation
- Accessories required for recirculated extraction: Recirculating kit
- Electronic controls
- with one-way flap: prevents outside air from entering your kitchen
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

* In accordance with the EU-Regulation No 65/2014

