


Serie | 8, HEADER2.Electric_Hob, 60 cm, Black PKN675DB1A







Optional accessories

 $\label{eq:HEZ390090:Wok Set consisting of 3 Items} \\$

The glass-ceramic radiant hob: makes cooking and cleaning especially easy.

- DirectSelect Premium: spacious and intuitive touch interface.
- **ReStart:** if something boils over, the cooktop automatically turns itself off and saves the last selected setting.
- Timer with switch-off function: Conveniently turns off the assigned cooking zone after the set time.
- **ChildLock:** locks the control panel to prevent accidental changes in settings.
- Energy consumption display: shows energy consumption for the most recent cooking process.

Technical Data

Product name/family: Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 4 Required niche size for installation (HxWxD) : 44 x 560-560 x

500-500 mm

Width of the appliance: 606 mm

Dimensions (HxWxD): 44 x 606 x 527 mm

Dimensions of the packed product (HxWxD) : 100 x 750 x 590

mm

Net weight: 8.099 kg Gross weight: 8.9 kg

Residual heat indicator : separate Location of control panel : Hob front Basic surface material : Ceramic

Color of surface : Black

Approval certificates: Australia Standards, CE, VDE

EAN code: 4242002843889

Electrical connection rating: 7500 W

Voltage: 220-240 V Frequency: 60; 50 Hz





Serie | 8, HEADER2.Electric_Hob, 60 cm, Black PKN675DB1A

The glass-ceramic radiant hob: makes cooking and cleaning especially easy.

- 60 cm: space for 4 pots or pans.

Flexibility of cooking zones

- Ring zone double: use regular or larger cookware on the expandable cooking zone.
- Cooking zone front left: 180 mm, 2 KW
- Cooking zone rear left: 170 mm, 265 mm, 1.8 KW
- Cooking zone rear right: 145 mm, 1.2 KW
- Cooking zone front right: 145 mm, 210 mm, 1 KW

Usage convenience

- Direct Select Premium Touch Control: directly control the power on the extra large illuminated touch bar (invisible when switched off).
- 17 power levels for each cooking zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function low setting for keeping food warm at the touch of a button: keep dishes warm at preset low power level.
- Timer with automatic switch off for all zones : switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- Alarm
- : an alarm sounds at the end of the time set (e.g. for pasta).
- Count-up timer
 - : shows how much time has passed since starting the timer (e.g. for potatoes).

Time saving & efficiency

- Automatic boil start heats the hotplate using the highest setting and then switches automatically to the lower setting previously selected.: boil water more quickly than at the highest regular power level.
- ReStart Quickly reinstates previous settings: in case of unintentional switch-off, restore all previous settings by switching on the cooktop again within 4 seconds.

Design

- Stainless steel side profiles with beveled front

Safety

- Digital 2-stage residual heat indicator: indicates which cooking zones are still hot or warm.
- Childproof lock: prevent unintended activation of the cooktop.
- WipeProtection: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Main switch: switch off all cooking zones at the touch of a button.
- Power on indicator: indicates if the hob is heating.
- Automatic safety switch-off: for safety reasons, heating stops after a preset time without interaction (customizable).
- Energy consumption display: shows the electricity consumption of the last cooking process.


Installation

- Dimensions of the product (HxWxD mm): 44 x 606 x 527
- Required niche size for installation (HxWxD mm) : 44 x 560 x (500 500)
- Min. worktop thickness: 16 mm
- Connected load: 7.5 KW



Serie | 8, HEADER2.Electric_Hob, 60 cm, **Black** PKN675DB1A

measurements in mm



- A: Minimum distance from the hob cut-out to the wall.
 B: Recessed depth
 C: With fitted oven underneath min. 20, possibly more; see space requirements for the oven.