QUICK REFERENCE GUIDE > HP90IDCHX4

Integrated Insert Rangehood, 90cm

Series 7 | Integrated

Stainless Steel and Glass




With edge-to-edge extraction, this rangehood is perfectly hidden away in your cabinetry.

- With three fan speeds plus a boost function, select the perfect extraction rate for your cooking
- Powerful maximum air movement of 780m³/hr
- Energy-efficient LED lighting to illuminate your cooking surface
- Wi-Fi enabled for notifications through the SmartHQ™ app

DIMENSIONS





FEATURES & BENEFITS

Achieve the invisible

This stylish rangehood fits seamlessly into your kitchen cabinetry, providing ventilation that is as discreet as it is powerful.

Effective extraction

Featuring three fan speeds, plus a boost function, this rangehood provides powerful extraction to quickly remove odours and steam. Odours can linger in the kitchen well after cooking is finished so the timer keeps the hood working for up to 15 minutes before automatically turning off.

Easy cleaning

Designed for simple removal, the filters are easy to clean and dishwasher safe, while the glass and stainless steel finish is easily wiped clean. The SmartHQ $^{\text{TM}}$ app will notify you when to clean the filter to ensure you get the best performance out of your rangehood.

Quality materials

This rangehood comes in a sleek black glass finish with a real stainless steel frame.

Full surface lighting

Low energy, dimmable LED lights provide superb illumination of the entire cooking surface.

SPECIFICATIONS

Accessories

Aluminium filter 792943

Accessories (sold separately)

Eave ducting kit PD-RHK150E
Light bulb requires service to replace
Recirculation carbon filter 793599
Roof ducting kit PD-RHK150T
Side wall ducting kit PD-RHK150W

Fan ratings

Maximum air movement 810m³/hr

Installation and cleaning

Dishwasher safe filters 2

Ducted Top extraction

Recirculation Optional - top extraction

QUICK REFERENCE GUIDE > HP90IDCHX4 Date: 20.11.2023 > 2

Performance			
Extraction type	Perimeter		
Fan speeds Filter type Number of filters	3 Mesh with perimeter 2		
		Power requirements	
		Supply frequency	50Hz
Supply voltage	220 - 240V		
Product dimensions			
Depth	280mm		
Height	316mm		
Width	830mm		
Product information			
Product information Control type	Capacitive touch		
	Capacitive touch		
Control type	Capacitive touch		
Control type Ventilation features	Capacitive touch •		
Control type Ventilation features Auto-off/Run-on timer	Capacitive touch .		
Ventilation features Auto-off/Run-on timer Dimmable lights	Capacitive touch		
Control type Ventilation features Auto-off/Run-on timer Dimmable lights Filter cleaning alert	•		
Ventilation features Auto-off/Run-on timer Dimmable lights Filter cleaning alert Light type	•		
Ventilation features Auto-off/Run-on timer Dimmable lights Filter cleaning alert Light type Timer function	•		

SKU 50190

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



Service & Warranty



User Guide Integrated Insert Rangehood



Installation Guide Integrated Insert Rangehood

Preliminary Specification Guide Rangehood



Data Sheet Insert Rangehood

